



# DIGITAL PANEL INDICATORS

Innovation In Motion

# INNOVATION IN MOTION

## Universal input Indicators - DMP200 series

The DMP200 series of universal input indicators offer unparalleled price and performance and are ideal for industrial test and process applications. Surface mount and microprocessor technology has enabled powerful features to be packed into a 1/8 DIN case. The measurement performance is significantly better than that normally associated with indicators in this price range. Applications range from simple measurement only to more demanding situations requiring digital communications, alarms, maths functions and complex signal conditioning. The powerful menu-driven software enables fast flexible set-up from the front panel or via the serial communications interface. No adjustment of internal potentiometers, internal links or plug-in cards is necessary.

The units are primarily suited for use with the Penny & Giles range of rotary or linear position sensors, but can also be configured to accept any one of over 20 different input types, including thermocouple, RTD, mA, mV and 10V signals.

### User linearisation

Linearisation curves can be defined using up to 24 calibration points entered manually or directly from the sensor output. The indicator will use the stored values to define the linearisation curve.



### Rugged enclosure

The enclosure uses flame retardant (VO) materials and the front panel conforms to IP65 (NEMA 4). The instrument can be removed from the panel without disturbing the connections.

### Connectivity

Digital status inputs, serial communications, analogue output, transmitter supply, alarm relays, transducer supply, are all available.



## Selection Guide

*Penny + Giles offers the widest choice of options to suit your application.*

**Model DML220 and DML340 are available from stock**



DMP210 page 4

4 digit indicator  
Universal input



DMP220 page 4

4 digit indicator  
Dual alarm relays  
Universal input



EMC

The products detailed in this document have been tested to the requirements of EN50081-1 (Emissions) and EN50082-2 (Immunity).



#### Quality Assurance

Penny + Giles are accredited to BS EN ISO9001:2000

Quality is at the heart of all our systems ensuring the reliability of our products from initial design to final despatch.

Registered No. 924881

# DIGITAL PANEL INDICATORS

## Features


- 'Fast-Cal' calibration
- Adjustable display resolution
- Maximum / minimum memory
  - Isolated analogue output
  - Two logic inputs
- Front panel function buttons
- Transducer excitation supply
- High speed analogue output
- Universal mains power supply
  - Serial communications
  - Dual alarm relays
  - Quad TTL alarm outputs
- Compatible with Penny & Giles LVDTs

## LVDT input Indicators - DML300 series

The DML300 series of digital panel indicators are designed for use with LVDT transducers. They are ideal for industrial and test applications and feature a five digit variable brightness LED display, a fast (125Hz) unscaled analog output for monitoring fast changes, a separate electrically isolated 0-10 Vdc/4-20mA scaleable output, serial 2 or 4 wire RS 422/485 communications interface, two logic control inputs to allow remote control of user selectable functions and two front panel push buttons that can be user defined to allow fast access to pre-programmed functions. The 'Fast-Cal' feature provides a fast, simple method of calibrating an indicator to the transducer at any two stroke positions. As LVDT transducers can only be calibrated in situ, the sensor is set to the mechanical low (zero) and then the high (span) positions when prompted by the DML300. The measured LVDT signal values are then stored, with their relevant display values, as the calibration parameters. The DML300 also automatically sets the correct input gain to suit the transducer output. Displayed values can be in any measurement units.

## Clear display

The flat, slightly recessed high brightness LED display, ensures maximum visibility even in difficult ambient conditions.



## Front panel control

Set-up is facilitated by the front panel buttons and a password protected menu. Two of the buttons can be user programed to provide one or more special functions.



## Total reliability

Surface mount and microprocessor technology has enabled powerful features to be packed into a 1/8 DIN case. No maintenance is necessary.



**DMP230** page 4

5 digit indicator  
Analogue output  
Serial output  
Logic status  
Universal input



**DMP240** page 4

5 digit indicator  
Dual alarm relays  
Analogue output  
Serial output  
Logic status  
Universal input



**DML330** page 6

5 digit indicator  
LVDT input



**DML340** page 6

5 digit indicator  
Dual alarm relays  
LVDT input



**DML350** page 6

5 digit indicator  
Quad TTL outputs  
LVDT input

# DMP200 SERIES

## DISPLAY

|             |   |
|-------------|---|
| Type        | 14.7mm high, high brightness red LED                              |
| Range       | -19999 to +99999 (DMP230, DMP240) -1999 to +9999 (DMP210, DMP220) |
| Update Rate | 2 per second  |

## A/D CONVERTER

|                                       |                           |
|---------------------------------------|---------------------------|
| Dual slope integrating with auto zero |                           |
| Conversion rate                       | 10 per second             |
| Resolution                            | 16 bit + sign (1 $\mu$ V) |
| Common mode rejection                 | > 150dB                   |
| Series mode rejection                 | > 70dB (50 or 60Hz)       |

## VOLTAGE INPUTS

|                 |   |
|-----------------|---|
| Ranges          | $\pm 100$ mV, $\pm 10$ V                            |
| Accuracy        | 0.05% of reading $\pm 20$ $\mu$ V (typically 0.02%) |
| Resolution      | 1 $\mu$ V (100mV range), 100 $\mu$ V (10V range)    |
| Input impedance | > 100M $\Omega$ (mV i/p) > 1M $\Omega$ (V i/p)      |

## CURRENT INPUT

|                 |  |
|-----------------|--|
| Range           | $\pm 20$ mA  |
| Accuracy        | 0.05% of reading $\pm 4$ $\mu$ V (typically 0.02%) |
| Resolution      | 2.0 $\mu$ A  |
| Input impedance | 5 $\Omega$ typical                                 |
| Maximum burden  | 100mV  |

## REFERENCE JUNCTION COMPENSATION (CJC)

|          |  |
|----------|--|
| Accuracy | Better than $\pm 0.5^{\circ}$ C after 30 minutes |
|----------|--|

## RESISTANCE/RTD INPUTS

|                    |  |
|--------------------|--|
| Configuration      | 2, 3 or 4 wire programmable            |
| Excitation current | 0.25mA typical                         |
| Range              | 0-400 $\Omega$                         |
| Accuracy           | 0.4 $\Omega$ (typically 0.2 $\Omega$ ) |
| Resolution         | 0.01 $\Omega$                          |

## THERMOSENSOR BREAK DETECTION

|              |                  |
|--------------|------------------|
| Programmable | Up or down scale |
|--------------|------------------|

## TRANSMITTER/TRANSDUCER SUPPLIES

|                                   |   |
|-----------------------------------|---|
| Isolation                         | 500Vdc/peak ac                                |
| 24V transmitter supply            | All models nominally 24V@ 32mA maximum        |
| 10V regulated transducer supply   | DMP210, DMP220 10V $\pm 0.1$ V @ 30mA maximum |
| 0-12V regulated transducer supply | DMP230, DMP240                                |
| Resolution                        | 0.01V   |
| Accuracy                          | $\pm 0.05$ V (typically 0.02V)                |
| Temperature drift                 | < 100ppm / $^{\circ}$ C                       |
| Output Ripple                     | < 5mV   |
| Output Current                    | 35mA maximum                                  |

## ALARMS

Each type of the DMP200 series has four software alarms. These can be configured by the user for alarm type, setpoint, on/off delay and on/off hysteresis value. Alarms can be individually set to be latching or non-latching and to flash a message on the front panel display when active. Any of the four software alarms can operate a relay (models DMP220 and DMP240 only). In addition a special AND function allows a relay to switch only if two or more alarm conditions are active.

## ALARM RELAYS

(DMP220 AND DMP240 ONLY)

2 off single change over (form C) contacts. Rated 1A @ 250Vac 5A @ 30Vdc  
Relays can be configured to be energised or de-energised in the alarm condition.

## DIGITAL STATUS INPUTS

(DMP230 AND DMP240 ONLY)

One or more of the stated functions can be user assigned to either of the two digital inputs which can be activated by external volt-free contacts:  
Tare, auto zero, display hold, display maximum, display minimum, display average, display test, Reset max/min & average (to the current measured value), alarm disable, alarm acknowledge, analogue output hold, keyboard lock.

## FUNCTION KEYS

One or more of the stated functions can be user assigned to either of the two front panel function buttons:  
Tare, auto zero, display hold, display maximum, display minimum, display average, display test, reset max/min & average (to the current measured value)

## ANALOGUE OUTPUT

DMP230, DMP240

|                        |   |
|------------------------|---|
| Isolation              | 500Vdc/peak ac                          |
| Ranges                 | User selectable 0-10V, 0-20mA or 4-20mA |
| Accuracy               | 0.2% of span (typically 0.1%)           |
| Temperature drift      | < 100ppm / °C                           |
| Output ripple          | < 10mV                                  |
| Response               | 63% within 32mS, 99% within 100mS       |
| Resolution             | 0.05% of span (5mV or 0.01mA)           |
| Maximum voltage output | 11V @ 22mA                              |
| Maximum current output | 22mA @ 18V                              |
| Maximum load           | 900Ω                                    |
| Output damping filter  | Programmable                            |

## SERIAL COMMUNICATIONS

DMP230, DMP240

|           |   |
|-----------|---|
| Type      | RS422/485, 2 or 4 wire multidrop                          |
| Isolation | 500Vdc/peak ac  |
| Speed     | 1200, 2400, 4600, 9600 Baud                               |
| Parity    | Odd, even or none   |
| Stop bits | 1 or 2  |
| Protocols | User selectable for MODBUS™ (RTU or ASCII) J-BUS and DTP1 |

## MATHS

|           |  |
|-----------|--|
| Max / Min | Stores maximum and minimum display values                                      |
| Averaging | Calculates average value over a user defined period between 1 and 9999 seconds |

## POWER REQUIREMENTS

|           |   |
|-----------|---|
| Universal | 90 to 265Vac 50 or 60Hz @ 10VA nominal or 10 to 32Vac or dc |
|-----------|---|

## ENVIRONMENTAL

|             |  |
|-------------|--|
| Temperature | 10° to 50°C (operating) -10° to 70°C (storage) |
| Humidity    | 0-95% RH non condensing                        |
| Protection  | Front panel to IP65 (NEMA 4)                   |

## PHYSICAL

|                    |                                 |
|--------------------|---------------------------------|
| Panel mount        | 1/8 DIN panel mount             |
| Dimensions         | 48mm (H) x 96mm (W) x 173mm (D) |
| Panel cut-out      | 44mm (H) x 92mm (W)             |
| Depth behind panel | 166mm including terminals       |
| Weight             | 0.4kg (0.55kg packed weight)    |

## SAFETY AND EMC

|                |   |
|----------------|---|
| Safety         | EN61010, IEC1010  |
| Susceptibility | ESD to IEC801-2, EN50082-1. Fast Transient burst to IEC801-4, Radiated to IEC801-3. |
| Emissions      | To EN50081-1; EN50022 Class A for radiated and conducted                            |
| CE certified   | 1995  |

## ORDERING CODE

**DMP210** - 4 digit indicator only - no alarm outputs  
**DMP220\*** - 4 digit indicator with dual alarm relays  
**DMP230** - 5 digit indicator with analogue output, serial output, logic status  
**DMP240** - 5 digit indicator with dual alarm relays, analogue output, serial output, logic status

**Power**    **1** = 90 to 265Vac 50 or 60Hz    **2** = 10 to 32Vac or dc

Please state model number, power requirements and quantity.

|  |       |   |   |  |  |  |   |  |  |
|--|-------|---|---|--|--|--|---|--|--|
| <table border="1"><tr><td>D</td><td>M</td><td>P</td><td></td><td></td><td></td></tr></table> | D     | M | P |  |  |  | <table border="1"><tr><td></td><td></td></tr></table> |  |  |
| D  | M     | P |   |  |  |  |   |  |  |
|  |       |   |   |  |  |  |   |  |  |
| model number   | power |   |   |  |  |  |   |  |  |

\* preferred model held in stock for rapid despatch

# DML300 SERIES

## DISPLAY

|                        |   |
|------------------------|---|
| Type                   | 14.7mm high, high brightness red LED    |
| Range                  | -19999 to +99999                        |
| Decimal point position | User selectable                         |
| Update rate            | User selectable 2, 4 or 10 per second   |
| Filter                 | User adjustable, 0 (off) to 999 seconds |

## LVDT INPUT

|                        |   |
|------------------------|---|
| Input voltage range    | 0.05V to 5Vrms  |
| Gain ranges            | 1, 5, 10 & 100  |
| Non linearity          | Automatic or manual gain setting facilities               |
| Temperature drift      | < $\pm 0.02\%$  |
| Stability              | < $\pm 0.005\%$ FSO / °C                                  |
| Transducer supply      | < $\pm 0.01\%$ FSO after 15 minutes                       |
| Supply frequency       | Selectable 3.0 or 5Vrms @ 25mA                            |
| Measurement resolution | User selectable 2.5 or 5.0kHz                             |
| Measurement rate       | Better than 1 part in 120,000                             |
| Measurement modes      | 10 readings per second                                    |
|                        | User selectable 4 wire differential or 5 wire ratiometric |

## ALARMS

|             |   |
|-------------|---|
| Setpoints   | Alarms can be quickly adjusted during normal running via the front panel buttons or by password protected menus (user selectable)   |
| Alarms      | Can be flashed on the display with the measured value.  |
| Alarm menus | 4, each individually user selectable for: high, low or deviation alarm action; high and low band limits (deviation action only); on and off delay timers; on and off hysteresis; and latching or non-latching |

## ALARM RELAYS

(DML340 ONLY)

2 off single change over (form C) contacts. Rated 1A @ 240Vac 5A @ 30Vdc  
Relays can be configured to be energised or de-energised in the alarm condition

## TTL ALARM OUTPUTS

(DML350 ONLY)

4 off TTL open collector.  
Alarm outputs can be configured to be energised or de-energised in the alarm condition

## STATUS (LOGIC) INPUTS

One or more of the stated functions can be user assigned to either of the two logic inputs:

Tare, auto (offset) zero, display hold, analogue output hold, display max, display min, display average, display test, reset (latched) alarms, reset max/min & average (to the current measured value), 'Enter' button lock (disables entry to configuration menus), alarm inhibit and *Fast-Cal* calibration enable

## Logic switching

The logic inputs can be switched by external volt free contacts or a TTL signal

## FUNCTION KEYS

One or more of the stated functions can be user assigned to either of the two front panel function buttons:  
Tare, zero, display hold, display max, display min, display average, display test, reset (latched) alarms, Reset max/min & average (to the current measured value), *Fast-Cal* calibration enable

## HIGH SPEED ANALOGUE OUTPUT

### Output filter

This is a buffered output giving a fast response from the LVDT demodulator output. The signal amplitude is dependant on the transducer excitation and the amount of sensor travel.

-3dB @ 125Hz

## ISOLATED ANALOGUE OUTPUT

|                        |   |
|------------------------|---|
| Isolation              | 500Vdc/peak ac                                  |
| Output                 | User selectable 0-10V, 0-20mA or 4-20mA         |
| Scaling                | User selectable (e.g. 4 to 20mA = 3.0 to 5.0mm) |
| Accuracy               | Better than 0.2%                                |
| Temperature drift      | < 100ppm / °C                                   |
| Response               | 63% within 32mS, 99% within 100mS               |
| Resolution             | 0.05% (5mV or 0.01mA)                           |
| Maximum voltage output | 11V @ 22mA                                      |
| Maximum current output | 22mA @ 18V                                      |
| Maximum load           | 900Ω  |
| Output damping filter  | Programmable                                    |

## FAST-CAL CALIBRATION

Automatically calibrates and matches the indicator to a connected LVDT transducer. The DML300 reads the transducer's output at any two sensor positions. The two measured values are stored as the calibration parameters. Calibration can be performed at any time.

## SERIAL COMMUNICATIONS

|           |   |
|-----------|---|
| Type      | RS422/485, 2 or 4 wire multidrop                          |
| Isolation | 500Vdc/peak ac  |
| Speed     | 1200, 2400, 4600, 9600 Baud                               |
| Parity    | Odd, even or none   |
| Stop bits | 1 or 2  |
| Protocols | User selectable for MODBUS™ (RTU or ASCII) J-BUS and DTPI |

## MATHS

|           |  |
|-----------|--|
| Max / Min | Stores maximum and minimum display values                                      |
| Averaging | Calculates average value over a user defined period between 1 and 9999 seconds |

## POWER REQUIREMENTS

|           |  |
|-----------|--|
| Universal | 90 to 265Vac 50 or 60Hz @ 12VA nominal |
|-----------|--|

## ENVIRONMENTAL

|             |  |
|-------------|--|
| Temperature | 10° to 50°C (operating) -10° to 70°C (storage) |
| Humidity    | 0-95% RH non condensing                        |
| Protection  | Front panel to IP65 (NEMA 4)                   |

## PHYSICAL

|                    |                                 |
|--------------------|---------------------------------|
| Panel mount        | 1/8 DIN panel mount             |
| Dimensions         | 48mm (H) x 96mm (W) x 173mm (D) |
| Panel cut-out      | 44mm (H) x 92mm (W)             |
| Depth behind panel | 166mm including terminals       |
| Weight             | 0.4kg (0.55kg packed weight)    |

## SAFETY AND EMC

|                |  |
|----------------|--|
| Safety         | EN61010  |
| Susceptibility | EN50082-1 & 2  |
| Emissions      | To EN50081-1 & 2; EN50022 Class A for radiated and conducted |
| CE certified   | 1997   |

## ORDERING CODE

**DML330** - LVDT Indicator with no Alarm Outputs  
**DML340\*** - LVDT Indicator with Dual Alarm Relays  
**DML350** - LVDT Indicator with Quad TTL Outputs

Please state model number and quantity.

|   |   |   |  |  |  |
|---|---|---|--|--|--|
| D | M | L |  |  |  |
|---|---|---|--|--|--|

model number

\* preferred model held in stock for rapid despatch