



	FX 600	FX 800	FX 1000	FX 1200	FX 1400	FX 1600	FX 1800	FX 2000	FX 2500	FX 2900	FX 3200	FX 3700	FX 4200	FX 5000	FX 5800	FX 7000	FX 8000	FX 10000	FX 12000	FX 15000
Peso escavatore (t) Carrier weight (t) Poids de l'engin porteur (t) Trägergewicht (t) Peso excavadora (t)	8-15	9-16	12-21	14-22	16-24	20-29	22-30	23-34	27-35	28-45	30-47	35-50	37-57	40-70	45-80	50-100	60-110	70-140	80-170	100-200
Peso martello (kg) Weight (kg) Poids (kg) Gewicht (kg) Peso (kg)	650	850	1050	1200	1400	1600	1750	2000	2500	2900	3200	3700	4400	4850	5800	7000	7800	9500	12000	14700
Altezza con utensile standard (mm) Height with standard tool (mm) Hauteur avec outil standard (mm) Höhe inkl. Standardmeißel (mm) Altura con puntero estándar (mm)	1900	2000	2050	2400	2600	2700	2800	3000	3200	3300	3400	3500	3800	4000	4200	4400	4500	4800	5200	5500
Diametro dell'utensile (mm) Chisel diameter (mm) Diamètre de l'outil (mm) Meißeldurchmesser (mm) Diámetro del puntero (mm)	95	105	115	120	120	135	135	150	150	160	160	175	180	195	200	215	215	235	255	280
Portata olio rich. (l/min.) Required oil supply (l/min.) Débit d'huile nécessaire (l/min.) Erforderliche Ölmenge (l/Min.) Caudal del aceite (l/min.)	70-100	90-130	135	140	105-145	130-160	140-175	165-190	180-205	180-240	200-260	250-300	270-320	290-350	300-380	350-420	380-440	430-510	480-570	500-650
Pressione dell'olio regolata al martello (bar) Oil pressure adjusted to the hammer (bar) Pression de l'huile vers le marteau (bar) Betriebsdruck (bar) Presión del aceite en el martillo (bar)	160	160	165	170	170	180	180	180	180	180	180	180	190	190	190	200	200	200	200	200
Numero dei colpi / min. Blows per minute Coups par minute Schlagzahl / Min. Número de golpes/min.	600-900	450-700	450-750	400-900	400-900	400-800	400-800	400-800	350-650	350-700	300-650	300-650	300-650	250-550	250-550	200-550	200-550	200-550	200-550	200-550
Energia del colpo (J) Energy per blow (J) Energie par coup (J) Schlagzahl/(J) Energía del golpe (J)	2000	2800	3000	3200	3700	4200	4800	5400	6500	8500	9000	9500	12500	16500	18500	22000	23000	25000	28000	35000
Contropressione max (bar) Max. back pressure (bar) Contre-pression maxi (bar) Max. Gegendruck (bar) Contrapresión max. (bar)	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
Diametro tubo entrata Inner diam. IN hose Diam. intérieur tuyau H.P. Innendurchm. Hammervorlauf Diám. interior manguera presión	3/4"	1"	1"	1"	1"	1"	1"	1"	1"	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/2	1" 1/2
Diametro tubo uscita Inner diam. OUT hose Diam. intérieur tuyau B.P. Innendurchm. Hammerrücklauf Diám. interior manguera retorno	3/4"	1"	1"	1"	1"	1"	1"	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/4	1" 1/2	1" 1/2