



## HOP

### FUNCTIONAL CHARACTERISTICS

|                              |                    |
|------------------------------|--------------------|
| Display                      | DIGITAL            |
| Supply                       | ELECTRIC           |
| Timer                        | -                  |
| Number of motors             | 1                  |
| Motor speeds                 | 1                  |
| Max cooking temperature (°C) | 260°C              |
| Core probe                   | -                  |
| Cooking chamber material     | AISI 304           |
| Opening door                 | FROM RIGHT TO LEFT |

### STANDARDS

|               |    |
|---------------|----|
| Certification | CE |
|---------------|----|

## TRAYS

|               |        |
|---------------|--------|
| Trays rack    | BASKET |
| Max tray load | 3kg    |

## DIMENSIONS

|                                     |                 |
|-------------------------------------|-----------------|
| Oven size with handle WxDxH (mm)    | 701 x 783 x 549 |
| Oven size without handle WxDxH (mm) | 701 x 723 x 549 |
| Chamber size WxDxH (mm)             | 454 x 304 x 305 |
| Unit weight (Kg)                    | 44              |

## PACKAGING

|                                 |                      |
|---------------------------------|----------------------|
| Packaging                       | PALLET + PAPER BOARD |
| Packaging size WxDxH (mm)       | 750 x 950 x 606      |
| Unit weight with packaging (Kg) | 67                   |
| Crate packaging size (optional) | -                    |

## ELECTRICAL DATA

|                       |            |
|-----------------------|------------|
| Heaters 4,5kW 50/60Hz |            |
| Power                 | 3,3kW      |
| Frequency             | 50/60Hz    |
| Power supply          | 220-240V ~ |
| Amperage              | 14,4A      |
| Power cord req.       | 3G1,5      |

## WATER CONNECTION REQUIREMENTS

|                                    |     |
|------------------------------------|-----|
| Humidification Water inlet         | -   |
| Washing Water inlet                | -   |
| Water drain                        | YES |
| Max water hardness                 | 5°f |
| Water pressure requirement min-max | -   |

## CONSUMPTION

|                            |   |
|----------------------------|---|
| Humidification Water       | - |
| Rinse Water @2barG         | - |
| Short Washing Water @2barG | - |
| Long Washing Water @2barG  | - |
| Short Washing Detergent *  | - |
| Long Washing Detergent *   | - |

## CONNECTIVITY

|           |     |
|-----------|-----|
| USB       | 2.0 |
| Bluetooth | -   |
| Wi-Fi     | -   |
| Cloud     | -   |

## ACCESSORIES

|   |            |
|---|------------|
| Self clean system kit   | -          |
| Oven stand  | T7         |
| Wheels kit for stand  | R60B       |
| Hood (Air)  | H7V        |
| Hood (Water)  | -          |
| Core probe  | -          |
| Proofer   | -          |
| Stacking kit for 2 ovens  | SK31       |
| Smoker  | -          |
| Blast chiller   | -          |
| Blast chiller stacking kit                                      | -          |
| Water softner cover   | WS10       |
| Water softner 6800L   | WS11       |
| Water softner 12000L  | WS12       |
| Water pressure adapter  | WPA        |
| Water shower kit  | 85KIT00001 |
| Detergent 750ML<br>(for Self clean system or Manual shower kit) | DT1        |
| Detergent 6KG   | DT2        |
| Detergent 10KG  | DT4        |