

**Fire-brigade
cranes**

**LTM 1070-4.2
LTM 1050-3.1**



LIEBHERR

8 t recovery winch, trailer coupling, shackles mounted at rear of carrier frame



Toolboxes at carrier, can be loaded from the top or the side



Driver's cab with various additional fire-brigade equipment



Load cross-beam 25 t, 3-axle-fire-brigade crane



Experience the Progress.

Fire-brigade cranes from Liebherr



Liebherr-Werk Ehingen GmbH
Postfach 1361, 89582 Ehingen, Germany
☎ +49 73 91 5 02-0, Fax +49 73 91 5 02-33 99
www.liebherr.com, E-mail: info.lwe@liebherr.com
www.facebook.com/LiebherrConstruction

he

iebherr.



External power supply 230 V,
connection for air pressure,
nearside



Various working floodlights



Martin fire-brigade horns,
blue rotating beacons

LIEBHERR

Lifting capacities on telescopic boom

		11 – 50 m		360°		10 t		EN		LTM 1070-4.2																	
		11 m		14,6 m		18,2 m		21,8 m		25,4 m		28,9 m		32,5 m		36,1 m		39,7 m		43,3 m		46,9 m		50 m			
m		*																								m	
2,5	68,5																										2,5
3	59,9	50,8	50,7	48,8																							3
3,5	53,1	46,1	46	46,2	38,9	31,9																					3,5
4	47,4	42	42	42,2	38,1	31,4	25,6																				4
4,5	42	38,3	38,3	38,4	37,3	31	25,3	20,6																			4,5
5	37,4	35	35,3	35,2	35,1	30,4	25,1	20,5	16,3																		5
6	30,5	29,8	30,2	30,4	30,3	28,9	24,5	20,1	16,1																		6
7	25,2	25,1	25,6	25,8	25,8	24,5	22,9	19,6	16	13	10,2																7
8	21,2	21,2	22	22	21,7	20,5	19,1	17,9	15,8	12,8	10,1	8															8
9			18,4	18,9	18,4	17,3	16,5	15,9	14,8	12,6	9,9	7,9	6,7														9
10			15,3	15,7	15,8	15,2	14,7	14	13,3	12,2	9,7	7,8	6,6														10
12			11,1	11,6	11,8	11,8	11,6	11	10,5	9,8	9,1	7,5	6,5														12
14				8,9	9,2	9,4	9,2	9,1	8,6	8,3	7,7	7,1	6,2														14
16				7,1	7,5	7,5	7,4	7,5	7,2	6,8	6,7	6,2	5,9														16
18					6,2	6,2	6,3	6,2	6,1	5,9	5,6	5,2	5														18
20						5,1	5,3	5,2	5,1	4,9	4,7	4,3	4,1														20
22							4,4	4,5	4,4	4,3	4,1	3,9	3,6	3,4													22
24								3,8	3,7	3,7	3,5	3,3	3	2,8													24
26								3,3	3,2	3,1	3	2,8	2,5	2,4													26
28									2,7	2,6	2,5	2,3	2	1,9													28
30									2,3	2,2	2,1	1,9	1,7	1,6													30
32										1,9	1,7	1,6	1,3	1,3													32
34											1,4	1,3	0,9	0,9													34
36												1,2	1														36

* over rear

Lifting capacities above 53,5 t only with additional pulley block.

t_189_20004_00_001

		11,4 – 38 m		360°		4,4 t		EN		LTM 1050-3.1							
		11,4 m		16,7 m		22 m		27,3 m		32,6 m		35,8 m		38 m			
m																m	
3	42		24,7		24,6		17										3
3,5	39,6		25,8		24,9		16,8										3,5
4	35,9		26,5		25,1		16,6	11,5									4
4,5	32,6		27,2		24,8		16,3	11,4									4,5
5	29,4		27,7		24,2		16	11,3	9,5								5
6	23,9		24,3		22,4		15,3	11	9,4	7,5							6
7	19,3		19,7		18,9		14,4	10,7	9,2	7,2							7
8	15,6		16		15,5		13,4	10,2	8,9	7							8
9			13,3		13,1		12,3	9,7	8,5	6,7							9
10			11		11,2		10,7	9,2	8,1	6,5							10
12			7,9		8,1		8,2	7,9	7,3	6							12
14					6,2		6,3	6,3	6,1	5,6							14
16					4,9		5	5,1	5	4,9							16
18					3,9		3,9	4	3,9	3,9							18
20							3,2	3,2	3,2	3,2							20
22							2,6	2,7	2,7	2,6							22
24							2,1	2,2	2,2	2,2							24
26								1,8	1,8	1,8							26
28								1,4	1,4	1,5							28
30									1,1	1,2							30
32										0,9							32

t_185_00128_00_000