



## T033DI.EV

<b>CAPACITY, DIMENSIONS, WEIGHT</b>	///
Capacity trays	3 TRAYS 450x340
Distance between trays (mm)	75
Type of rack holder	GRID
Unit size with handle WxDxH (mm)	560 x 652 x 455
Unit size without handle WxDxH (mm)	560 x 602 x 455
Chamber size WxDxH (mm)	474 x 381 x 245
Packaging	CARTON BOX
Packaging size WxDxH (mm)	600 x 700 x 560
Unit weight (kg)	27
Unit weight with packaging (kg)	32
<b>ELECTRICAL DATA</b>	///
Number of engines	1
Frequency (Hz)	50
Power (kW)	3,2
Voltage A	-
B	-
C	230V ~
D	-
Current (A) A	-
B	-
C	13,9
D	-

Power cord/power plug	A
	B
	C
	D
<b>WATER CONNECTION REQUIREMENTS</b>	///
Water inlet	YES
Water drain	-
Minimum water quality standards	5° f
<b>FUNCTIONAL CHARACTERISTICS</b>	///
Supply	ELECTRIC
Certification	-
Control panel	DIGITAL
Multilingual screen	-
Cooking type	CONVECTION
Bidirectional motors	YES
Two speed regulation	-
Max cooking temperature (°C)	260
Cooking chamber material	AISI 430
Opening door	FROM TOP TO BOTTOM
Easy clean internal glass	-
<b>STANDARD EQUIPMENT</b>	///
Self clean system	-
Core probe	-
<b>VARIANTS AVAIABLES</b>	///
Certification	-
Unit size with handle WxDxH (mm)	-
Unit size without handle WxDxH (mm)	-
Frequency (Hz)	60
Power (kW)	-
Voltage	A -
	B -
	C -
	D -
Current (A)	A -
	B -
	C -
	D -
Power cord / power plug	A -

	B	-
	C	-
	D	-
Packaging		-
Packaging size WxDxH (mm)		-
<b>ACCESSORIES</b>		///
Self clean system		-
Stainless steel tray rack holder		-
Stainless steel grid rack holder		"3 TRAYS GN 2/3 67mm"
Oven stand		T6
		T6S
		T6SL
Wheels kit for stand		R60B
Condensation hood		CK01
Water condensation hood		-
Proofer		CA6008M0
		CA6008MH
		CA6008DH
Overlapping kit for 2 ovens		SK6
Blast chiller		KDA03
		KDA05
		ASP05
Overlapping kit for blast chillere + 1 ovens		-
Smoker		-
Core probe		-
Core probe for vacuum		-
Water softner cover		WS10
Water softner 6800L		WS11
Water softner 12000L		WS12
Water pressure adaptor		WPA
Manual shower kit		-
"Detergent 750ML (for Self clean system or Manual shower kit)"		-
"Detergent 6KG (only with self clean system)"		-
"Detergent 10KG (only with self clean system)"		-
		-

## FEATURES

◆ Standard | ◇ Optional | - Not available

### MANUAL COOKING

Convection cooking	30°C - 260°C	◆
Mixed humidity and convection cooking	90°C - 230°C	◆
Humidity		-

### AUTOMATIC COOKING

Program: possibility to memorize program	99	◆
V-EVOLUTION CONTROL WITH 6 SPEED PROGRAMS		-
Cooking cycles for each program	n°4	◆
Automatic pre-heating setting		◆

### AIR DISTRIBUTION IN THE COOKING CHAMBER

V-BI.DIRETIONAL REVERSING FAN		◆
V-POWERFULL ENGINE		◆
Number of speed regulation		-

### OVERLAP SYSTEM

V- OVERLAP CONNECTION with ovens		◇
V- OVERLAP CONNECTION with Venix's Proofing		◇
V- OVERLAP CONNECTION with Venix's Stand		◇

### OTHER FUNCTIONS

Infinity time		◆
Temperature parameter unit F° or C°		◆
V - LIGHTS	Halogen	◆
USB		-

### TECHNICAL DETAILS

Internal glass easy clean system		◆
Thermal insulation structure (energetic efficiency)		◆
Humidity regulation	Digital	◆