



eptarefrigeration

DRINK & DAIRY

CABINET
COLLECTION



Epta

PLUG-IN POWER AND SWITCH ON YOUR BUSINESS

Since 1983, IARP is the brand that has been able to establish itself in the world of **commercial refrigeration** for the **Food&Beverage and Ho.re.ca sectors**, thanks to its high level of **specialization in the production of incorporated plug-in cabinets.**

The brand joined the **Epta Group in March 2013** to complete the Group's offer with a **range of products** that set themselves apart in the **universe of plug-in refrigeration.**

Plug-in power summarises, in the communicative strength of the plug symbol, the philosophy and distinctive traits of the IARP offer with its high standing in terms of **reliability, quality and innovative capacity.**

In short, the Plug-in-Power claim expresses all of the features, performances and power of aesthetic attraction that enable these refrigerated cabinets to **“turn on” and maximise the interest of consumers** towards the products on display and the brands behind them.



EVOLVED, FLEXIBLE AND RELIABLE IDEAS

With an **exclusive style**, that responds to the requirements of **product personalization**, IARP produces ad hoc furnishing that satisfies the **need for versatility and flexibility** in displaying products in a variety of different kinds of commercial spaces, in order to actively involve consumers and **drive acquisition processes**. From this perspective the IARP brand is able to offer **evolved ideas that reflect market trends**.

The products, produced on an ad hoc basis, are personalized with **graphics that are studied in depth** and created by an in-house Team of professionals and printers, to fully reflect the institutional image of the company or the specific products on display.

It is also thanks to **its reliability** that the IARP brand is recognised as a specialist at a global level in the conservation and display of industrial ice-cream. All of the production phases are overseen step by step by competent staff and are subjected to the most stringent quality tests, as demonstrated by the **ISO 9001 and 14001 certifications**.

EFFICIENCY AND SUSTAINABILITY: AN IMPORTANT DEVELOPMENT DRIVER

The competitiveness of IARP involves improving in a constant manner **the performance of its products** with an ever-improved **optimization of energy consumption, in full respect of environmental resources.**

IARP always aims at continually **updating its know-how and improving its technology.**

For this reason it chooses **new generation refrigerating gases** with a low environmental impact, eco compatible materials, colours, chemical products and raw materials, all of which are selected in accordance with the **REACH regulation.**

EptaService: GREAT EXPERTISE AT YOUR SERVICE

The high qualitative standing of IARP is supported by the **EptaService which strength is the maintenance, management of spare parts and the complete refurbishment of cabinets and display units.**

The broad **EptaService** is a truly complete offer: from the cleaning of the products to the replacement of parts with specific spare parts, to the full refurbishment of display units, so as to ensure on the one hand, the best performances during the life cycle of the cabinet, and on the other, the truly exclusive possibility to renew and make the plug-in even more attractive for a new season of business.



DRINK&DAIRY

COUNTER

- COUNTER 21 GLASS SILVER / BLACK, COUNTER 50 GLASS SILVER / BLACK, COUNTER 68 GLASS SILVER / BLACK, COUNTER 98 GLASS SILVER / BLACK .8

IMPULSE

- CILY 50 P with Lights, JAZZ 56 P .10
- JOY 30 LITE SUSHI / MEAT, JOY 30 PRIME SUSHI / MEAT .11
- JOY 30 LITE DARK SMARTSCREEN

VERTICAL

- STILL SLIM WHITE, STILL SLIM BLACK .14
- BITTER 42 WHITE, BITTER 42 BLACK .15
- FIZZ 42 WHITE, FIZZ 42 BLACK .16
- GLEE 42 LITE .17
- GLEE GLASS 42, GLEE GLASS WINERY .18
- EIS 104.2, EIS 112.3, EIS 162 HP .19

WINERY

- BITTER W&B, BITTER WOOD W&B .22
- MAGENTA 408 2T WINE COOLER, SCARLET 298 2T WINE COOLER, SCARLET 298 WINE COOLER, CORAL .23







COUNTER


COUNTER 21 GLASS SILVER

COUNTER 50 GLASS BLACK

COUNTER 68 GLASS SILVER

COUNTER 98 GLASS BLACK

OPTIONS (EXTRA)
 personalization with logo


| DATI TECNICI / TECHNICAL SPECIFICATIONS | COUNTER 21 GLASS | COUNTER 50 GLASS | COUNTER 68 GLASS | COUNTER 98 GLASS |
|---|--|--|--|--|
| Temperatura / Temperature | 0° ÷ +7°C | 0° ÷ +7°C | 0° ÷ +7°C | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 350x419x488 | 435x500x494 | 435x500x680 | 480x500x845 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 21 - 18 | 52 - 38 | 68 - 65 | 98 - 93 |
| Refrigerazione / Cooling System Sistema di Sbrinamento / Defrosting System | Statica / Static Automatico / Automatic | Statica / Static Automatico / Automatic | Statica / Static Automatico / Automatic | Statica / Static Automatico / Automatic |
| Classe Climatica / Climatic Class | K1 / CC2 | K1 / CC21 | K1 / CC2 | K1 / CC2 |
| Gas Refrigerante / Refrigerant Gas | R600a | R600a | R600a | R600a |
| Illuminazione Interna / Internal Light | LED | LED | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 0.75 | 0.85 | 0.85 | 1.00 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 16.5 - 15 | 22 - 20 | 26 - 24 | 31 - 29 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 456x524x582 | 521x581x559 | 521x581x744 | 562x581x897 |
| Carico / Loading Camion Bilici | 504 | 416 | 312 | 192 |
| Standard Trailer Capacity (L 13.60 mt) | 504 | 416 | 312 | 288 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. | n.a. | n.a. | n.a. |
| Container 20" (ft) | n.a. | 172 | 129 | 80 |
| Container 40" (ft) | n.a. | 344 | 258 | 164 |
| Container 40" (ft) HC | 480 | n.a. | n.a. | n.a. |

A close-up photograph of a shopping cart filled with various groceries. In the foreground, there is a large orange plastic jug, a white plastic jug with a blue cap, and a dark glass bottle of soda. To the left, there is a loaf of bread, a head of lettuce, and a bunch of bananas. The background shows a blurred supermarket aisle with shelves of products.

IMPULSE


CILY 50 P with Lights

JAZZ 56 P

OPTIONS (EXTRA)
 personalization with logo

CILY 50 P with Lights

JAZZ 56 P
DATI TECNICI / TECHNICAL SPECIFICATIONS

| | | |
|---|------------------|------------------------|
| Temperatura / Temperature | +1° ÷ +9 °C | -1° ÷ 5°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 440x440x850 | 560x744x1110 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 50 - 46 | 163 - 65 |
| Refrigerazione / Cooling System | Statica / Static | Ventilata / Ventilated |
| Sistema di Sbrinamento / Defrosting System | Manuale / Manual | Automatico / Automatic |
| Classe Climatica / Climatic Class | K4 / CC1 | 4 / M1 |
| Gas Refrigerante / Refrigerant Gas | R600a | R290 |
| Illuminazione Interna / Internal Light | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 0.86 | 4.80 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 23 - 21 | 69 - 63 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 486x486x935 | 670x800x1270 |
| Carico / Loading | | |
| Camion Bilici | 270 | 60 |
| Standard Trailer Capacity (L 13.60 mt) | 270 | 60 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | 405 | 120 |
| Container 20" (ft) | 96 | 23 |
| Container 40" (ft) | 192 | 48 |
| Container 40" (ft) HC | n.a. | 96 |



JOY 30 LITE SUSHI / MEAT



JOY 30 PRIME SUSHI / MEAT



JOY 30 LITE DARK SMARTSCREEN



OPTIONS (EXTRA)
personalization with logo



| DATI TECNICI / TECHNICAL SPECIFICATIONS | JOY 30 LITE / PRIME SUSHI / MEAT | JOY 30 LITE DARK SMARTSCREEN |
|--|--|--|
| Temperatura / Temperature | -1° ÷ +7°C | -1° ÷ +5°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 623x739x1490 | 623x739x1490 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 330 - 163 | 330 - 163 |
| Refrigerazione / Cooling System Sistema di Sbrinamento / Defrosting System | Ventilata / Ventilated Automatico / Automatic | Ventilata / Ventilated Automatico / Automatic |
| Classe Climatica / Climatic Class | 3 / M1 | 3 / M1 |
| Gas Refrigerante / Refrigerant Gas | R290 | R290 |
| Illuminazione Interna / Internal Light | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | LITE 12.00 - PRIME 12.40 | 12.40 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 112 - 97 | 112 - 97 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 660x790x1615 | 660x790x1615 |
| Carico / Loading Camion Bilici Standard Trailer Capacity (L 13.60 mt) Mega Trailer Capacity (L 13.60 mt x H 3 mt) | 60 60 n.a. | 60 60 n.a. |
| Container 20" (ft) Container 40" (ft) Container 40" (ft) HC | 22 51 n.a. | 22 51 n.a. |





VERTICAL



STILL SLIM WHITE



STILL SLIM BLACK



OPTIONS (EXTRA)
personalization with logo



DATI TECNICI / TECHNICAL SPECIFICATIONS

STILL SLIM WHITE / BLACK

| | |
|---|------------------------|
| Temperatura / Temperature | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 435x517x1832 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 195 - 170 |
| Refrigerazione / Cooling System | Ventilata / Ventilated |
| Sistema di Sbrinamento / Defrosting System | Automatico / Automatic |
| Classe Climatica / Climatic Class | K1 / CC1 |
| Gas Refrigerante / Refrigerant Gas | R600a |
| Illuminazione Interna / Internal Light | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 2.02 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 79 - 73 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 450x558x1965 |
| Carico / Loading | |
| Camion Bilici | 110 |
| Standard Trailer Capacity (L 13.60 mt) | 110 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. |
| Container 20" (ft) | 52 |
| Container 40" (ft) | 105 |
| Container 40" (ft) HC | 105 |



BITTER 42 WHITE



BITTER 42 BLACK



OPTIONS (EXTRA)
personalization with logo



DATI TECNICI / TECHNICAL SPECIFICATIONS

BITTER 42 WHITE / BLACK

| | |
|---|------------------------|
| Temperatura / Temperature | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 590x629x1817 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 378 - 365 |
| Refrigerazione / Cooling System | Ventilata / Ventilated |
| Sistema di Sbrinamento / Defrosting System | Automatico / Automatic |
| Classe Climatica / Climatic Class | K1 / CC1 |
| Gas Refrigerante / Refrigerant Gas | R600a |
| Illuminazione Interna / Internal Light | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 1.96 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 80 - 72 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 614.5x680x1956.5 |
| Carico / Loading | |
| Camion Bilici | 66 |
| Standard Trailer Capacity (L 13.60 mt) | 66 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. |
| Container 20" (ft) | 27 |
| Container 40" (ft) | 57 |
| Container 40" (ft) HC | n.a. |



FIZZ 42 WHITE



FIZZ 42 BLACK



OPTIONS (EXTRA)
personalization with logo


DATI TECNICI / TECHNICAL SPECIFICATIONS
FIZZ 42 WHITE / BLACK

| | |
|---|------------------------|
| Temperatura / Temperature | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 590x629x2006 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 378 - 365 |
| Refrigerazione / Cooling System | Statica / Static |
| Sistema di Sbrinatorio / Defrosting System | Automatico / Automatic |
| Classe Climatica / Climatic Class | K1 / CC1 |
| Gas Refrigerante / Refrigerant Gas | R600a |
| Illuminazione Interna / Internal Light | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 2.25 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 80 - 72 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 614x680x2148.4 |
| Carico / Loading | |
| Camion Bilici | 66 |
| Standard Trailer Capacity (L 13.60 mt) | 66 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. |
| Container 20" (ft) | 27 |
| Container 40" (ft) | 57 |
| Container 40" (ft) HC | n.a. |



GLEE 42 LITE



OPTIONS (EXTRA)
personalization with logo



DATI TECNICI / TECHNICAL SPECIFICATIONS

GLEE 42 LITE

| | |
|---|------------------------|
| Temperatura / Temperature | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 670x625x1964 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 410 - 258 |
| Refrigerazione / Cooling System | Ventilata / Ventilated |
| Sistema di Sbrinamento / Defrosting System | Automatica / Automatic |
| Classe Climatica / Climatic Class | K1 / CC2 |
| Gas Refrigerante / Refrigerant Gas | R290 |
| Illuminazione Interna / Internal Light | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 3.00 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 128 - 119 |
| Dimensioni Imballo LxPxA (mm) Packaging Dimensions WxDxH (mm) | 700x690x2120 |
| Carico / Loading | |
| Camion Bilici | 57 |
| Standard Trailer Capacity (L 13.60 mt) | 57 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. |
| Container 20" (ft) | 24 |
| Container 40" (ft) | 51 |
| Container 40" (ft) HC | n.a. |





GLEE GLASS 42



GLEE GLASS WINERY


OPTIONS (EXTRA)
 personalization with logo


| DATI TECNICI / TECHNICAL SPECIFICATIONS | GLEE GLASS 42 | GLEE GLASS WINERY |
|---|------------------------|------------------------|
| Temperatura / Temperature | 0° ÷ +7°C | 0° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 670x625x1964 | 670x625x1964 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 410 - 258 | 410 - 258 |
| Refrigerazione / Cooling System | Ventilata / Ventilated | Ventilato / Ventilated |
| Sistema di Sbrinatorio / Defrosting System | Automatico / Automatic | Automatica / Automatic |
| Classe Climatica / Climatic Class | K1 / CC2 | K1 / CC2 |
| Gas Refrigerante / Refrigerant Gas | R290 | R290 |
| Illuminazione Interna / Internal Light | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 3.0 | 3.0 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 128 - 119 | 129 - 121 |
| Dimensioni Imballo LxPxH (mm) Packaging Dimensions WxDxH (mm) | 700x690x2120 | 700x690x2120 |
| Carico / Loading | 57 | 57 |
| Camion Biliici | 57 | 57 |
| Standard Trailer Capacity (L 13.60 mt) | 57 | 57 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. | n.a. |
| Container 20" (ft) | 24 | 24 |
| Container 40" (ft) | 51 | 51 |
| Container 40" (ft) HC | n.a. | n.a. |



EIS 104.2



EIS 112.3



EIS 162 HP


OPTIONS (EXTRA)
 personalization with logo


| DATI TECNICI / TECHNICAL SPECIFICATIONS | EIS 104.2 | EIS 112.3 | EIS 162.3 |
|---|------------------------|------------------------|------------------------|
| Temperatura / Temperature | -1° ÷ +7°C | -1° ÷ +7°C | -1° ÷ +7°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 1110x792x2000 | 1250x786x2032 | 1875x786x2035 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | 1040 - 750 | 1240 - 870 | 1890 - 1310 |
| Refrigerazione / Cooling System | Ventilata / Ventilated | Ventilato / Ventilated | Ventilato / Ventilated |
| Sistema di Sbrinatorio / Defrosting System | Automatico / Automatic | Automatica / Automatic | Automatica / Automatic |
| Classe Climatica / Climatic Class | 4 / M2 | 4 / M2 | 4 / M2 |
| Gas Refrigerante / Refrigerant Gas | R290 | R290 | R290 |
| Illuminazione Interna / Internal Light | LED | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 4 / Ambient 30°C RH 55%) | 7.50 | 6.20 | 8.20 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 197 - 184 | 216 - 196 | n.a. |
| Dimensioni Imballo LxPxH (mm) Packaging Dimensions WxDxH (mm) | 1130x850x2060 | 1280x840x2170 | 1980x910x2200 |
| Carico / Loading | | | |
| Camion Biliici | 32 | 26 | 14 |
| Standard Trailer Capacity (L 13.60 mt) | 32 | 26. | 14 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. | n.a. | n.a. |
| Container 20" (ft) | 14 | 11 | 6 |
| Container 40" (ft) | 28 | 23 | 13 |
| Container 40" (ft) HC | n.a. | n.a. | n.a. |





WINERY


BITTER W&B

BITTER WOOD W&B


OPTIONS (EXTRA)
personalization with logo


DATI TECNICI / TECHNICAL SPECIFICATIONS

Temperatura / Temperature
 Dimensioni Mobile LxPxA (mm)
 Cabinet Dimensions WxDxH (mm)
 Volume Lordo - Netto (Lt)
 Gross - Net Volume (Lt)
 Refrigerazione / Cooling System
 Sistema di Sbrinamento / Defrosting System
 Classe Climatica / Climatic Class
 Gas Refrigerante / Refrigerant Gas
 Illuminazione Interna / Internal Light
 Consumo Energetico / Energy Consumption
 (kW/24h - Class 3 / Ambient 25°C RH 60%)
 Peso Lordo / Netto (Kg)
 Gross / Net Weight (Kg)
 Dimensioni Imballo LxPxA (mm)
 Packaging Dimensions WxDxH (mm)
 Carico / Loading
 Camion Bilici
 Standard Trailer Capacity (L 13.60 mt)
 Mega Trailer Capacity (L 13.60 mt x H 3 mt)
 Container 20" (ft)
 Container 40" (ft)
 Container 40" (ft) HC

BITTER W&B / BITTER WOOD W&B

0° ÷ +20°C
 593x599x1838
 375 - 250
 Ventilata / Ventilated
 Automatico / Automatic
 K1 / CC2
 R600a
 LED
 2.25
 94 - 90
 630x675x1945
 63
 63
 n.a.
 27
 57
 n.a.



MAGENTA 408 2T WINE COOLER



SCARLET 298 2T WINE COOLER



SCARLET 298 WINE COOLER



CORAL


OPTIONS (EXTRA)
 personalization with logo


| DATI TECNICI / TECHNICAL SPECIFICATIONS | MAGENTA 408 2T WINE COOLER | SCARLET 298 2T WINE COOLER | SCARLET 298 WINE COOLER | CORAL |
|---|----------------------------|----------------------------|-------------------------|------------------------|
| Temperatura / Temperature | +5° ÷ +12°C / +12° ÷ +20°C | +5° ÷ +12°C / +12° ÷ +20°C | +5° ÷ +20°C | +5° ÷ +18°C |
| Dimensioni Mobile LxPxA (mm) Cabinet Dimensions WxDxH (mm) | 598x690x1610 | 598x690x1210 | 598x690x1210 | 431x597.5x875.5 |
| Volume Lordo - Netto (Lt) Gross - Net Volume (Lt) | Netto / Net 393 | Netto / Net 275 | Netto / Net 285 | Netto / Net 118 |
| Refrigerazione / Cooling System | Ventilata / Ventilated | Ventilata / Ventilated | Ventilata / Ventilated | Ventilata / Ventilated |
| Sistema di Sbrinamento / Defrosting System | Automatico / Automatic | Automatico / Automatic | Automatico / Automatic | Automatico / Automatic |
| Classe Climatica / Climatic Class | SN / N / ST | SN / N / ST | SN / N / ST | SN / ST |
| Gas Refrigerante / Refrigerant Gas | R600a | R600a | R600a | R600a |
| Illuminazione Interna / Internal Light | LED | LED | LED | LED |
| Consumo Energetico / Energy Consumption (kW/24h - Class 3 / Ambient 25°C RH 60%) | 0.142 - 0.698 | 0.127 - 0.678 | 0.136 - 0.676 | 0.140 - 0.654 |
| Peso Lordo / Netto (Kg) Gross / Net Weight (Kg) | 91 - 82 | 78 - 70 | 77 - 69 | 38 - 34 |
| Dimensioni Imballo LxPxH (mm) Packaging Dimensions WxDxH (mm) | 655x780x1700 | 655x780x1300 | 655x780x1300 | 485x700x935 |
| Carico / Loading | | | | |
| Camion Bilici | 60 | 60 | 60 | 162 |
| Standard Trailer Capacity (L 13.60 mt) | 60 | 60 | 60 | 162 |
| Mega Trailer Capacity (L 13.60 mt x H 3 mt) | n.a. | n.a. | n.a. | n.a. |
| Container 20" (ft) | 25 | 25 | 25 | 72 |
| Container 40" (ft) | 51 | 51 | 51 | 144 |
| Container 40" (ft) HC | n.a. | n.a. | n.a. | n.a. |





Epta

www.iarp-plugin.com



Follow us on:      by Epta

Rev. JAN 2024